

Phone: 916.683.7111  
Fax: 916.691.941

Web: [www.elkgrovecity.org](http://www.elkgrovecity.org)

8401 Laguna Palms Way  
Elk Grove, California 95758



## City of Elk Grove Drainage Notes

1. ALL CONSTRUCTION AND MATERIALS FOR DRAINAGE SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE CITY OF ELK GROVE IMPROVEMENT STANDARDS AND STANDARD CONSTRUCTION SPECIFICATIONS. WHERE DISCREPANCIES EXIST, APPROPRIATE NOTES SHALL BE ADDED TO THE PLANS, TAKING PRECEDENCE OVER THE STANDARD CONSTRUCTION SPECIFICATIONS.
2. THE MINIMUM COVER REQUIREMENTS DURING CONSTRUCTION FOR TEMPORARY CONSTRUCTION VEHICLE LOADING SHALL BE 4-FEET FOR METAL AND PLASTIC PIPE, AND 3-FEET FOR REINFORCED CONCRETE PIPE.
3. THE CONTRACTOR SHALL PLACE THE PROPER STRENGTH PIPE IF TRENCH CONDITIONS ENCOUNTERED DIFFER FROM THE DESIGN TRENCH.
4. STORM DRAIN PIPES IN THE PUBLIC RIGHT-OF-WAY (ROW) AND DRAINAGE EASEMENTS SHALL CONFORM TO THE STANDARD CONSTRUCTION SPECIFICATIONS:
  - DRAINAGE PIPE MATERIAL SHALL CONFORM TO SECTION 36 AND SECTION 50 (EXCLUDING 50-20, WHICH IS NOT ALLOWED).
  - DRAINAGE MANHOLES SHALL CONFORM TO SECTION 39.
5. STORM DRAIN PIPES SHALL BE TESTED IN CONFORMANCE WITH THE STANDARD CONSTRUCTION SPECIFICATIONS:
  - DRAINAGE PIPES, INCLUDING DRAIN INLET LATERALS, SHALL BE TESTED IN CONFORMANCE WITH SECTION 38-9.
  - STORM DRAIN MANHOLES SHALL BE TESTED IN CONFORMANCE WITH SECTION 39-4.01.
6. RESILIENT CONNECTORS, IN CONFORMANCE WITH SECTION 39-2.01 AND STANDARD DRAWING (STD. DWG.) SD-7 OF THE STANDARD CONSTRUCTION SPECIFICATIONS, ARE REQUIRED BETWEEN PRE-CAST MANHOLE AND PIPE, AND BETWEEN PRE-CAST DROP INLET AND PIPE. WATER STOPS ARE REQUIRED FOR PIPE TO CAST-IN-PLACE MANHOLE/ DROP INLET CONNECTIONS.
7. EROSION CONTROL STRUCTURES (STD. DWGS. SD-26, SD-27, SD-28.1, SD-28.2, SD-28.3, AND SD-28.4) SHALL BE CLASS B CONCRETE, NOT GROUTED COBBLE.

Phone: 916.683.7111  
Fax: 916.691.941

Web: [www.elkgrovecity.org](http://www.elkgrovecity.org)

8401 Laguna Palms Way  
Elk Grove, California 95758



8. ALL DRAINAGE INLETS IN THE PUBLIC ROW AND DRAINAGE EASEMENTS SHALL HAVE A PERMANENT STORM DRAIN MESSAGE “NO DUMPING – FLOWS TO CREEK” OR OTHER APPROVED MESSAGE CONSISTENT WITH SECTION 11-15 AND STD. DWGS. SQ-10.1 AND SQ-10.2 OF THE CITY OF ELK GROVE IMPROVEMENT STANDARDS.